

PUNJAB POLLUTION CONTROL BOARD

Zonal Office-I, E-648-B, Focal Point, Phase-5, Ludhiana

Website:- www.ppcb.gov.in

Office Dispatch No:Registered/Speed PostDate:Industry Registration ID:R15LDH22317679Application No:16182208

To,

Vikram Dhingra

G.t. Road Vill. Khakat, Shanewal

Ludhiana, Punjab-141120

Subject: Grant Varied 'Consent to Operate' u/s 21 of Air (Prevention & Control of Pollution) Act, 1981 for discharge

of emissions arising out of premises.

With reference to your application for obtaining Varied 'Consent to Operate' u/s 21 of Air (Prevention & Control of Pollution) Act, 1981, you are hereby, authorized to operate an industrial unit for discharge of the emission(s) arising out of your premises subject to the Terms and Conditions as mentioned in this Certificate.

1. Particulars of Consent to Operate under Air Act, 1981 granted to the industry

| Consent to Operate Certificate No. | CTOA/Varied/LDH2/2021/16182208 | |
|------------------------------------|---|--|
| Date of issue : 18/08/2021 | | |
| Date of expiry : | 31/03/2026 | |
| Certificate Type : | Varied | |
| Previous CTO No. & Validity : | R15LDH2CTOA3332071 From:03/12/2015 To:30/06/2020 | |

2. Particulars of the Industry

| Name & Designation of the Applicant | Vikram Dhingra, (Proprietor) |
|-------------------------------------|---|
| Address of Industrial premises | Toolman Industries Of India, G.t. Road Vill. Khakat, Shanewal, Ludhiana East,Ludhiana Ii-141120 |
| Capital Investment of the Industry | 817.76 lakhs |
| Category of Industry | Orange |
| Type of Industry | 2063-Steel and steel products using various furnaces like blast furnace /open hearth furnace/induction furnace/arc furnace/submerged arc furnace /basic oxygen furnace /hot rolling reheated furnace |
| Scale of the Industry | Medium |
| Office District | Ludhiana Ii |
| Consent Fee Details | Rs. 1,29,600/- vide UTR No. 845669934 dated 23.02.2021(water) Rs. 1,44,000/- vide UTR No. 62321509 dated 23.02.2021 (Rs. 14400/- adjusting as NOC fees)(air) After taking penalty of Rs. 18000/- each |

| Raw Materials (Name with Quantity per day) | MS SCRAP @ 24000 Kgs/day, FERRO ALLOY @ 6000 Kgs/day, ALLOY STEEL SCRAP @ 30000 Kgs/day |
|--|--|
| Products (Name with Quantity per day) | STEEL INGOTS, ROUND BAR, FLAT & SQUARE @ 30000 Kgs/day |
| By-products, if any, (Name with Quantity per day) | Nil |
| Details of the machinery and process | As per application form |
| Quantity of fuel required (in TPD) and capacity of boilers/ Furnace/Thermo heater etc. | FURNACE OIL @ 50 Liter/day for 02 no. annealing furnace FURNACE OIL @ 120 Liter/day for 02 no. reheating furnace FURNACE OIL @ 120 Liter/day for 02 no. rolling mills HSD @ 100 Ltr/day for 02 no. D.G sets |
| Type of Air Pollution Control Devices to be installed | Common dust collector followed by pulsating jet bag filter house as APCD with induction furnaces wet scrubber as APCD with rolling mills D.G sets are placed in acoustic room |
| Stack height provided with each boiler/thermo heater/Furnace etc. | Stack of height 21 Mtr above ground level provided with Induction furnace Stack of height 21.33 Mtr above ground level provided with annealing furnaces Stack of height 18 Mtr above ground level provided with reheating furnaces Stack of height 18 Mtr above ground level provided with rolling mills Stack of height 3 Mtr above roof level provided with D.G see of capacity 160 KVA Stack of height 3 Mtr above roof level provided with D.G see of capacity 125 KVA |
| Sources of emissions and type of pollutants | 02 no. Induction furnaces of capacities 2 TPH & 1 TPH 02 no. reheating furnace 02 no. annealing furnace 02 no. rolling mills 02 no. D.G set of capacities 125 KVA & 160 KVA |
| Standards to be acheived under Air(Prevention & Control of Pollution) Act, 1981 | As prescribed by the Board/MoEF & CC, New Delhi |



(Ravinder Bhatti) Environmental Engineer

For & on behalf

of

(Punjab Pollution Control Board)

| Dated: |
|--------|
| |

A copy of the above is forwarded to the following for information and necessary action please:

Environmental Engineer, Punjab Pollution Control Board, Regional Office-2, Ludhiana for information and necessary action. He is requested to collect samples of stack emissions from all the stacks of the industry, within two months.



(Ravinder Bhatti) Environmental Engineer

For & on behalf

of

(Punjab Pollution Control Board)



TERMS AND CONDITIONS

A. GENERAL CONDITIONS

- 1. This consent is not valid for getting power load from the Punjab State Power Corporation Ltd. or for getting loan from the financial institutions.
- 2. The industry shall apply for renewal /extension of consent at least two months before expiry of the consent.
- 3. The industry shall not violate any of the norms prescribed under the Air (Prevention & Control of Pollution) Act, 1981, failing which, the consent shall be cancelled / revoked.
- 4. The achievement of adequacy and efficiency of the air pollution control devices installed shall be the entire responsibility of the industry
- 5. The authorized fuel being used shall not be changed without the prior written permission of the Board.
- 6. The industry shall not discharge any fugitive emissions. All gases shall be emitted through a stack of suitable height, as per the norms fixed by the Board from time to time.
- 7. The industry shall provide port-holes, platforms and/or other necessary facilities as may be required for collecting samples of emissions from any chimney, flue or duct or any other outlets.

Specifications of the port-holes shall be as under:-

i) The sampling ports shall be provided at least 8 times chimney diameter downstream and 2 times upstream from the flow disturbance. For a rectangular cross section the equivalent diameter (De) shall be calculated from the following equation to determine upstream, downstream distance:-

$$De = 2 LW / (L+W)$$

Where L= length in mts. W= Width in mts.

- ii) The sampling port shall be 7 to 10 cm in diameter
- 8. The industry shall put display Board indicating environmental data in the prescribed format at the main entrance gate.
- 9. The industry shall discharge all gases through a stack of minimum height as specified in the following standards laid down by the Board.

(i) Stack height for boiler plants

| S.NO. | Boiler with Steam Generating Capacity | Stack heights |
|-------|---------------------------------------|--|
| 1. | Less than 2 ton/hr. | 9 meters or 2.5 times the height of neighboring building which ever is more |
| 2. | More than 2 ton/hr. to 5 ton/hr. | 12 meters |
| 3. | More than 5 ton/hr. to 10 ton/hr | 15 meters |
| 4. | More than 10 ton/hr. to 15 ton/hr | 18 meters |
| 5. | More than 15 ton/hr. to 20 ton/hr | 21 meters |
| 6. | More than 20 ton/hr. to 25 ton/hr. | 24 meters |
| 7. | More than 25 ton/hr. to 30 ton/hr. | 27 meters |
| 8. | More than 30 ton/hr. | 30 meters or using the formula H = 14 Qg0.3or H = 74 (Qp)0.24 Where Qg = Quantity of SO2 in Kg/hr. Qp = Quantity of particulate matter in Ton/day. |

Note: Minimum Stack height in all cases shall be 9.0 mtr. or as calculated from relevant formula whichever is more.

- (ii) For industrial furnaces and kilns, the criteria for selection of stack height would be based on fuel used for the corresponding steam generation.
- (iii) Stack height for diesel generating sets:

| Capacity of diesel generating set | Height of the Stack | |
|-----------------------------------|------------------------|-----------|
| 0-50 KVA | Height of the building | + 1.5 mt |
| 50-100 KVA | -do- | + 2.0 mt. |
| 100-150 KVA | -do- | + 2.5 mt. |
| 150-200 KVA | -do- | + 3.0 mt. |
| 200-250 KVA | -do- | + 3.5 mt. |
| 250-300 KVA | -do- | + 3.5 mt. |

For higher KVA rating stack height H (in meter) shall be worked out according to the formula:

H = h + 0.2 (KVA)0.5

where h = height of the building in meters where the generator set is installed.

- 10. The pollution control devices shall be interlocked with the manufacturing process of the industry to ensure its regular operation.
- 11. The existing pollution control equipment shall be altered or replaced in accordance with the directions of the Board, and no pollution control equipment or chimney shall be altered or as the case may be erected or reerected except with the prior approval of the Board.
- 12. The industry will provide canopy and adequate stack with the D.G sets so as to comply with the provision of notification No GSR-371 E dated 17-5-2002(amended from time to time) issued by MOEF under Environment (Protection) Act, 1986.
- 13. The Govt. of Punjab, Department of Science, Technology & Environment vide its notification no.4/46/92-3ST/2839 dt. 29/12/1993 has put prohibition on the use of rice husk as fuel after 1.4.1995 except the following:-

�In the form of briquettes and use of rice husk in fluidized bed combustion. So the industry shall make the necessary arrangement to comply with the above notification. �

- 14. The industry shall submit balance sheet of every financial year to the concerned Regional Office by 30th June of every year
- 15. That the industry shall submit a yearly certificate to the effect that no addition / up-gradation/ modification/ modernization has been carried out during the previous year otherwise the industry shall apply for the varied consent.
- 16. a) The industry shall ensure that at any time the emission do not exceed the prescribed emissions standards laid down by the Board from time to time for such type of industry /emissions.
 - b) The industry shall ensure that the emissions from each stack shall conform to the following emission standards laid down by the Board in respect of the Industrial Boilers.

| Steam Generating capacity A. | Required particulate matter I | В. | |
|--|-------------------------------|-------------|--|
| Area upto 5 Km from Other than 'A' class Other than the periphery of I and Class-II town | | | |
| Less than 2 ton/hr. | 800 mg/NM3 | 1200 mg/NM3 | |
| 2 ton to 10 ton/hr. | 500 mg/NM3 | 1000 mg/NM3 | |
| Above 10 ton to 15 ton/hr | 350 mg/NM3 | 500 mg/NM3 | |
| Above 15 ton/hr | 150 mg/NM3 | 150 mg/NM3 | |

All emissions normalized to 12% carbon dioxide.

- 17. The industry shall ensure that the Hazardous Wastes generated from the premises are handled as per the provisions of the Hazardous Waste (Management, Handling and Transboundary Movement) Rules, 2008, without any adverse effect on the environment, in any manner.
- 18. The air pollution control equipments shall be kept at all time in good running condition and;

- (i) All failures of control equipments.
- (ii) The emissions of any air pollutant into the atmosphere in excess of the standards lay down by the Board occurring or being apprehended to occur due to accident or other unforeseen act or event. 'Shall be intimated through fax to the concerned Regional Office as well as to the Director of Factories, Punjab, Chandigarh as required under rule 10 of the Punjab State Board for the Prevention and Control of Air Pollution Rules, 1983'.
- 19. The industry shall plant minimum of three suitable varieties of trees at the density of not less than 1000 trees per hectare all along the boundary of the industrial premises.
- 20. The industry shall submit a site emergency plan approved by the Chief Inspector of Factories, Punjab as applicable.
- 21. The industry shall comply with the conditions imposed by the SEIAA/MOEF in the Environmental Clearance granted to it as required under EIA notification dated 14/9/06, if applicable.
- 22. The industry shall make necessary arrangements for the monitoring of stack emissions and shall get its emissions analyzed from lab approved / authorized by the Board:-
 - (i) Once in Year for Small Scale Industries.
 - (ii) Twice/thrice/four time in a Year for Large/Medium Scale Industries.
- 23. The industry shall maintain the following record to the satisfaction of the Board:
 - (i) Log books for running of air pollution control devices or pumps/motors used for it.
 - (ii) Register showing the result of various tests conducted by the industry for monitoring of stack emissions and ambient air.
 - (iii) Register showing the stock of absorbents and other chemicals to be used for scrubbers.
- 24. The industry will install the separate energy meter for running pollution control devices and shall maintain record with respect to operation of air pollution control device so as to the satisfy the Board regarding the regular operation of air pollution control device and monthly reading / record may be sent to the Board by the fifth of the following month.
- 25. The industry shall provide online monitoring system as applicable, for in stack emission and shall maintain the record of the same for inspection of the Board Officers.
- 26. The Board reserves the right to revoke the consent granted to the industry at any time, in case the industry is found violating the provisions of Air (Prevention & Control of Pollution) Act, 1981 as amended from time to time.
- 27. The industry shall comply with any other conditions laid down or directions issued in due course by the Board under the provisions of the Air (Prevention & Control of Pollution) Act, 1981.
- 28. Nothing in this consent shall be deemed to neither preclude the institution of any legal action nor relieve the applicant from any responsibilities, liabilities or penalties to which the applicant is or may be subjected to under this or any other Act.
- 29. Any amendments/revisions made by the Board/CPCB/MOEF in the emission/stack height standards shall be applicable to the industry from the date of such amendments/revisions.
- 30. The industry shall dispose off its solid waste generated by the burning of fuel in an Environmentally Sound Manner within the premises/outside as approved by the Board, to avoid public nuisance and air pollution problem in the area.
- 31. The industry shall ensure that no air pollution problem or public nuisance is created in the area due to the discharge of emissions from the industry.
- 32. The industry shall provide adequate arrangement for fighting the accidental leakage/discharge of any air pollutant/gas/ liquids from the vessels, mechanical equipment's etc, which are likely to cause environmental pollution.
- 33. The industry shall not change or alter the manufacturing process(es) and fuel so as to change the quality/quantity of emissions generated without the prior permission of the Board.
- 34. The industry shall earmark a land within their premises for disposal of boiler ash in an environmentally sound manner, and / or the industry shall make necessary arrangements for proper disposal of fuel ash in a scientific manner and shall maintain proper record for the same, if applicable.
- 35. The industry shall obtain and submit Insurance cover under the Public Liability Insurance Act, 1991.
- 36. The industry shall provide proper and adequate air pollution control arrangements for control emission from its fuel handling area, if applicable.

- 37. The industry shall comply with the code of practice as notified by the Government/Board for the type of industries where the siting guidelines / Code of Practice have been notified.
- 38. The industry shall not cause any nuisance/traffic hazard in vicinity of the area
- 39. The industry shall ensure that the noise & air emission from D.G. sets do not exceed the standards prescribed for D.G. sets by the Ministry of Environment & Forests, New Delhi.
- 40. The industry shall ensure that there will not be significant visible dust emissions beyond the property line
- 41. The industry shall provide adequate and appropriate air pollution control devices to contain emissions from handling, transportation and processing of raw material & product of the industry.
- 42. The Industry shall ensure that its production capacity does not exceed the capacity mentioned in the consent and shall not carry out any expansion without the prior permission / NOC of the Board.

